

ARMOR [LARGE]



27K/30K ONLY

PROJECT:
MODEL #:
FIXTURE TYPE:

STANDARD SPECIFICATIONS

HOUSING

The large sized Dark Sky cutoff wall pack design features a die-cast aluminum housing. The hinged door is fastened over the continuous rubber seal with stainless steel hardware.

REFLECTOR

Formed aluminum, secured in position with hardware.

LENS

Clear, tempered glass is held into the cast door with stainless steel brackets and a sturdy, rubber gasket.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

C37 - 35W nominal, .30 A input - 5017 lm. Dimmable (0-10V).

C49 - 45W nominal, .40 A input - 6761 lm. Dimmable (0-10V).

D30 - 30W nominal, .28 A input - 3070 lm. Non-dimming.

D56 - 56W nominal, .80 A input - 6135 lm. Non-dimming.

MOUNTING


The 7039 is designed to be mounted directly to the surface, and wired with rear conduit entry, or surface conduit into the side entry ports.

FINISH

This series is available in a standard bronze polyester powder coat.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.



ORDERING INFORMATION



WET



7039 - _____ - _____ - _____
 Model 2. 3. 4. (if required)

2. WATTAGE

- C37** 35W C Series LED
- C49** 45W C Series LED

- D30** 30W D Series LED
- D56** 56W D Series LED

3. COLOR TEMPERATURE

- 35K** 3500K standard color temperature
- 27K** 2700K color temperature (C Series only)
- 30K** 3000K color temperature (C Series only)
- 40K** 4000K color temperature (C Series only)

4. AVAILABLE OPTIONS

- BAC**¹ Buy American Compliant
- BBC** Integral Battery Backup, Cold Weather (C Series only)
- DTR**⁴ Triac (Line Voltage) Dimming (120V) (C Series only)
- ECW**⁵ Extreme Cold Weather (-40°C / -40°F min.)
- ES**⁶ ENERGY STAR® (C Series only)
- FCL**⁷ French Canadian Labels
- PO1** Photo Control (120V)
- PO2** Photo Control (208, 240, 277V)
- T24**⁹ Title 24 JA8 Compliant (C49 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED
2022.05.24