

# 7060 LED

## STANDARD SPECIFICATIONS

### HOUSING

The injection molded polycarbonate housing resists damage and is lightweight for smaller poles.

### DIFFUSER

The acorn is one of the most recognizable street lamps in use today. This classic design is molded from UV stabilized frosted acrylic.

### LED PLATFORM

The 7060 series utilizes Brownlee's proprietary LED tower platform, which consists of plug and play LED components positioned at a downward angle to maximize illumination on the ground and general area, while minimizing wasted up-light. All electrical components are serviceable.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
 Amperage rated @ 110V input  
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F  
 Refer to Wattage section for lumen output. Consult Brownlee.com for performance of all CCTs.

### MOUNTING

The 7060 series has a fitter designed for 3" outside diameter poles.

### FINISH

This series is available in a standard black polyester powder coat.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

|                      |
|----------------------|
| <b>PROJECT:</b>      |
| <b>MODEL #:</b>      |
| <b>FIXTURE TYPE:</b> |



## ORDERING INFORMATION

**7060** - \_\_\_\_\_ - \_\_\_\_\_  
 Model                      2.                      3. (if required)

### 2. WATTAGE


- B18LED** 18W B Series LED, .15 A input, 1850 delivered lumens  
Replaces up to 35W MH
- C37LED** 37W C Series LED, .37 A input, 3300 delivered lumens  
Replaces up to 50W MH

\*Delivered lumens noted in 3500K.

### 3. AVAILABLE OPTIONS

- 35K** 3500K standard color temperature
- 27K** 2700K color temperature
- 30K** 3000K color temperature
- 40K** 4000K color temperature
- BAC** Buy American Compliant
- ES** ENERGY STAR® (C37LED only)
- SRG** Surge Protection (10,000 A discharge current)

## FIELD INSTALLED ACCESSORIES (order separately)

| ORDERING NUMBER   | DESCRIPTION  | DIMENSIONS           | NOTES  |
|---|--|----------------------|--|
| <br>154204 | Wall Mounted Arm, Die-cast aluminum construction, Black polyester powder coat finish | 12.5"w x 6"h x 4.5"d | Must be mounted with anchors (by others) appropriate for the mounting surface (100 lb minimum support) |

**Specifications and dimensions subject to change without notice.**  
 Consult your Brownlee Lighting representative for availability and ordering information.