

7068 LED

STANDARD SPECIFICATIONS

HOUSING

Heavy duty die-cast aluminum design with an architectural flair for any decor.

DIFFUSER

This injection molded two piece acorn design is available in UV stabilized acrylic. The prismatic design delivers Type V distribution patterns.

LED PLATFORM

The 7068 series utilizes Brownlee's proprietary LED tower platform, which consists of plug and play LED components positioned at a downward angle to maximize illumination on the ground and general area, while minimizing wasted up-light. All electrical components are serviceable.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Amperage rated @ 110V input
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F
 Refer to Wattage section for lumen output. Consult Brownlee.com for performance of all CCTs.

MOUNTING

The 7068 series has a fitter designed for 3" outside diameter poles.

FINISH

This series is available in black polyester powder coat as standard, and in all Brownlee paints as an optional offering.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



CPA5 diffuser, BP finish



ORDERING INFORMATION

7068 - _____
 Model 2. 3. 4. 5. (if required)

2. FINISH

- STANDARD**
BP Black Polyester
- OPTIONAL**
AB Antique Bronze
AS Antique Silver
BT Brass Tone
BZ Bronze
DB Desert Bronze
GM Gun Metal
MB Metallic Bronze
NT Nickel Tone
PL Platinum
WH White

3. WATTAGE

- C49LED** 49W C Series LED, .40 A input, 4700 delivered lumens
 Replaces up to 70W MH
- C66LED** 66W C Series LED, .54 A input, 6600 delivered lumens
 Replaces up to 100W MH

*Delivered lumens noted in 3500K.

4. DIFFUSER



- CPA5** Clear Prismatic Acrylic - Type V

5. AVAILABLE OPTIONS

- 35K** 3500K standard color temperature
27K 2700K color temperature
30K 3000K color temperature
40K 4000K color temperature
BAC Buy American Compliant
DLR Downlight Reflector*
PO1 Photo Control (120V)
PO2 Photo Control (208, 240, 277V)
SRG Surge Protection (10,000 A discharge current)

*Downlight Reflector reduces uplight by 30-40% and increases downlight by 20-25%

FIELD INSTALLED ACCESSORIES (order separately)

ORDERING NUMBER	DESCRIPTION	DIMENSIONS	NOTES
 154204	Wall Mounted Arm, Die-cast aluminum construction, Black polyester powder coat finish	12.5"w x 6"h x 4.5"d	Must be mounted with anchors (by others) appropriate for the mounting surface (100 lb minimum support)
 154204XX	Wall Mounted Arm, Die-cast aluminum construction, Available in all Brownlee paint finishes (specify when ordering)	12.5"w x 6"h x 4.5"d	Must be mounted with anchors (by others) appropriate for the mounting surface (100 lb minimum support)

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

