

1022

DISCONTINUED

CHECK FACTORY STOCK

STANDARD SPECIFICATIONS

DIFFUSER

The one piece design is an injection molded, clear UV stabilized acrylic, with prismatic ribs running along the length. The diffuser also features a rubber gasket and molded threads, creating an effective seal when the jar is installed.

HOUSING

The housing consists of two pieces of durable injection molded aluminum that are bolted together to form a single, rust resistant housing.

ELECTRICAL

CFL, 2-pin GX23 Base 2700K lamp – 120V Magnetic NPF Ballast
GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start ballast. Fluorescent lamps powered by instant start or rapid start ballasts, and GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life.


MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 1022 series is available in a natural satin aluminum finish, or it can be painted in optional colors.

| |
|---------------|
| PROJECT: |
| MODEL #: |
| FIXTURE TYPE: |



WET

ORDERING INFORMATION

1022 - _____ - _____ - _____
 Model 2. 3. 4. (if required)

2. FINISH

SA **STANDARD**
 Satin Aluminum

BL **OPTIONAL**
WH Black
 White

CUSTOM
Provide color sample or RAL
code to match

3. WATTAGE

13 1-13W CFL, mag.

13G 1-13W GU24 CFL, elec. NPF

18G 1-18W GU24 CFL, elec. NPF

4. AVAILABLE OPTIONS

BAC Buy American Compliant
ES3 ENERGY STAR® (elec., NPF) (G only)

Specifications and dimensions subject to change without notice.
Consult your Brownlee Lighting representative for availability and ordering information.