

# EMBLEM DISCONTINUED

PROJECT:
MODEL #:
FIXTURE TYPE:

## STANDARD SPECIFICATIONS

### TRIM

Cold rolled steel, roll formed and assembled with hardware and white painted brackets that attach to the mount pan.

### DIFFUSER

Translucent, UV stabilized 0.125" white acrylic formed over a mold.

### PAN

Formed, cold rolled steel design finished with a powder coat high reflectance white paint.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
 Amperage rated @ 110V input  
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.



- B06 - 6W nominal, .05 A input - 586 lm. Non-dimming.
- B12 - 12W nominal, .10 A input - 1158 lm. Dimmable (0-10V).
- C09 - 9W nominal, .10 A input - 817 lm. Dimmable (0-10V).
- C17 - 16W nominal, .15 A input - 1674 lm. Dimmable (0-10V).
- C24 - 23W nominal, .20 A input - 2297 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The 1330 series is available in all Brownlee paint finishes as a standard offering.



### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

### ORDERING INFORMATION



**1330** - \_\_\_\_\_  
 Model                      2.                      3.                      4.                      5. (if required)

## 2. FINISH

### STANDARD

- AB Antique Bronze
- AS Antique Silver
- BL Black
- BZ Bronze
- DB Desert Bronze
- GM Gun Metal
- MB Metallic Bronze
- MG Metallic Gold
- NT Nickel Tone
- PL Platinum
- WH White

### CUSTOM

Provide color sample or RAL code to match

## 3. WATTAGE

- B06** 6W B Series LED
- B12** 12W B Series LED
- C09** 9W C Series LED
- C17** 16W C Series LED
- C24** 23W C Series LED

## 4. COLOR TEMPERATURE

- 35K** 3500K standard color temperature
- 27K** 2700K color temperature
- 30K** 3000K color temperature
- 40K** 4000K color temperature

## 5. AVAILABLE OPTIONS

- 90R<sup>0</sup>** 90 CRI (3000K only)
- BAC<sup>1</sup>** Buy American Compliant
- DTR<sup>4</sup>** Triac (Line Voltage) Dimming (120V) (All except B06)
- ES<sup>6</sup>** ENERGY STAR<sup>®</sup> (Not available in 90 CRI)
- FCL<sup>7</sup>** French Canadian Labels
- T24<sup>9</sup>** Title 24 Compliant (B12 & C24 in 3000K only)

**Notes:** (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

