

POLKA

DISCONTINUED
CONTACT FACTORY FOR
AVAILABILITY OR
ALTERNATES

STANDARD SPECIFICATIONS

FRAME

Cold rolled steel, roll formed and assembled with rivets. The assembly has multiple stiffening edges for durability.

DIFFUSER

Translucent, UV stabilized white acrylic. The material is flexible to withstand minor impact without breaking.

PAN

Formed, cold rolled steel design, finished with a powder coat high reflectance white paint.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 367 lm. Non-dimming.

B12 - 12W nominal, .10 A input - 726 lm. Dimmable (0-10V).

C09 - 9W nominal, .10 A input - 512 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1049 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 1439 lm. Dimmable (0-10V).

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 1387 series is available in all Brownlee paint finishes as a standard offering.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

1387 - - - - -
Model 2. 3. 4. 5. (if required)

2. FINISH

STANDARD	
AB	Antique Bronze
AS	Antique Silver
BL	Black
BZ	Bronze
DB	Desert Bronze
GM	Gun Metal
MB	Metallic Bronze
MG	Metallic Gold
NT	Nickel Tone
PL	Platinum
WH	White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

B06	6W B Series LED
B12	12W B Series LED
C09	9W C Series LED
C17	16W C Series LED
C24	23W C Series LED

4. COLOR TEMPERATURE


35K	3500K standard color temperature
27K	2700K color temperature
30K	3000K color temperature
40K	4000K color temperature

5. AVAILABLE OPTIONS

90R⁰	90 CRI (3000K only)
BAC¹	Buy American Compliant
BB1^{2*}	Integral Battery Backup
BLD^{3**}	Bi-Level Dimming (All except B06)
DTR⁴	Triac (Line Voltage) Dimming (120V) (All except B06)
ES⁶	ENERGY STAR® (Not available in 90 CRI)
FCL⁷	French Canadian Labels
OCC⁸	Occupancy Sensor
T24⁹	Title 24 JA8 Compliant (B12 & C24 in 3000K only)
TBC	Top/Bottom Covers (Perforated)



WH finish



DAMP



Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BB1/BB5/BB6 - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BB1, BB5, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BB1, BB5, BB6, BLD, DTR, ES, or FCL. (10) BB5 - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** *BB1/BB5/BB6 - standard BB1 (and BB5) option has a minimum operating temperature of 10C/50F. BB6 option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.