





1447 LED -

The 1447's trapezoidal form factor makes for a unique wall luminaire that is ADA compliant and perfect for any upscale commercial or residential application. The contemporary one-piece diffuser is constructed of thick, opal-white glass which is formed with a closed top. Architectural cast aluminum trim is standard in Brushed Nickel with a variety of optional finishes to choose from. Backplate matches the trim. Other models in this series include the 1440, 1442, and 1445.

FINISHES







CONTACT FACTORY FOR

PROJECT:					
MODEL #:					
FIXTURE TYPE:					

STANDARD SPECIFICATIONS

TRIM

Tapered die-cast aluminum trim piece attaches directly to the decorative backplate. Trim contains no exposed hardware.

DIFFUSER

Diffuser is constructed of 0.20" thick opal-white glass which is formed with a closed top. Diffuser seats securely into the trim and is held into position with a screw from the top.

REFLECTOR

Formed cold rolled steel design, finished in a powder coat high reflectance white paint.

DECORATIVE BAC¹KPLATE

Formed cold rolled steel rectangular backplate adds scale while serving as a sleek complement to the fixture.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Refer to Wattage section for lumen output. Consult Brownlee.com for performance of all CCTs.

MOUNTING


Directly to j-box (by others). Mounting hardware included.

FINISH

The 1447 series is finished in Brushed Nickel as a standard offering. Options include all Brownlee paint finishes.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.



BN finish



DAMP



ORDERING INFORMATION

1447 - ____ - ___ - ___ - ___ 5.

	Model 2.		3.	4.	5.		
2.	FINISH	3.	WATTAGE	4.	COLOR TEMPERATURE	5.	AVAILABLE OPTIONS
	STANDARD Brushed Nickel OPTIONAL Black Bronze Gun Metal Metallic Bronze Metallic Gold Nickel Tone Platinum White CUSTOM ide color sample or RAL to match	B06 B12 C09	6W B Series LED, .05 A input, 550 delivered lumens. Non-dimming. 12W B Series LED, .10 A input, 1063 delivered lumens. Dimmable (0-10V). 9W C Series LED, .10 A input, 750 delivered lumens. Dimmable (0-10V).	35K 27K 30K 40K	·	90R ⁰ BAC ¹ DTR ⁴ ES ⁶ FCL ⁷ T24 ⁹	Buy American Compliant Triac (Line Voltage) Dimming (120V) (All except B06) ENERGY STAR® (Not available in 90 CRI) French Canadian Labels

Universal Footnotes (only applies if option is listed on spec sheet): (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. 1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBJ, BBC, or DTR. (6) BC - cannot be combined with 90R or TZ4. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD to OCC. Add'l Notes: *BBI/BBC - BBI minimum operating temp: 100/50F unless otherwise stated. BBC minimum operating temp: 200/4F, **BBLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%.

2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches.

