# **CRESCEN** STANDARD SPECIFICATIONS

# DISCONTINUED CONTACT FACTORY FOR AVAILABILITY OR ALTERNATES

PROJECT:

7.5"

۲

6.5" MC

4"

13"

MODEL:

### FIXTURE TYPE:

#### TRIM

Cold rolled 16 GA steel, roll formed and welded assembly. The trim is bolted to the pan during final assembly.

#### DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is formed over an aluminum die and maintains a .08" thickness throughout.

## PAN

Cold rolled 20 GA steel, formed with die punch tooling.

#### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs. B06 - 6W nominal, .05 A input - 438 lm. Non-dimming. B12 - 12W nominal, .10 A input - 866 lm. Dimmable (0-10V). C09 - 9W nominal, .10 A input - 611 lm. Dimmable (0-10V).

#### MOUNTING

Directly to j-box (by others). Mounting hardware included.

#### FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

#### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

#### ORDERING INFORMATION

	<b>.68</b> 2.		<u> </u>		<b>-</b> 5. (if required)			
2.	FINISH	3.	WATTAGE		4.	COLOR TEMPERATURE	5.	AVAILABLE OPTIONS
BN	STANDARD Brushed Nickel	B06 B12	6W B Series LED 12W B Series LED		35K 27K 30K	3500K standard color temperature 2700K color temperature 3000K color temperature	90R <sup>0</sup> BAC <sup>1</sup> DTR <sup>4</sup>	90 CRI (3000K only) Buy American Compliant Triac (Line Voltage) Dimming (120V)(All
	OPTIONAL Black Bronze Gun Metal Metallic Bronze Metallic Gold Nickel Tone Platinum White CUSTOM ide color sample or RAL to match	C09	9W C Series LED		40K	4000K color temperature	ES <sup>6</sup> FCL <sup>7</sup> T24 <sup>9</sup>	except B06) ENERGY STAR <sup>®</sup> (Not available in 90 CRI) French Canadian Labels Title 24 JA8 Compliant (B12 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. 1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BLC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDS (do not combine with 90R option). Cannot be combined with BLD, eCW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC. Add' Notes: \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period. Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED 2021.08.06

**BN** finish

ADA

DAMP

SUPPORTS