1486

STANDARD SPECIFICATIONS

DISCONTINUED CHECK FACTORY STOCK

PROJECT:
MODEL #:
FIXTURE TYPE:

HOUSING

Cold rolled steel, formed in a die, finished with an electroplated brushed nickel coating that will withstand most nicks and scratches. The housing can be mounted vertical or horizontal.

DIFFUSER

Glass cylinder, white finished interior and etched exterior to disguise the light source. The cylinder is bonded with adhesive to a carbon steel threaded ring that screws into the cup holder for a secure installation.

ELECTRICAL

GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast GU24 LED, 2-prong Base 3000K lamp - 120V - Lifetime Rating: 25,000 hours

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.


 $\label{eq:GU24} GU24\ base\ compact\ fluorescent\ lamps\ used\ with\ an\ occupancy\ sensor\ may\ result\ in\ severely\ shortened\ lamp\ life\ and/or\ ballast\ damage.$

MOUNTING

The 1486 series is designed to be mounted directly to a j-box (by others). Mounting hardware included.

FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.







памр



ORDERING INFORMATION

 1486

 Model
 2.
 3.
 4.
 5. (if required)

2. FINISH

STANDARD

BN Brushed Nickel

OPTIONAL

BL Black BT Brass Tone ΒZ Bronze **GM** Gun Metal MB Metallic Bronze NT Nickel Tone PL Platinum WH White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

G27LED 2-7W GU24 LED - 900 lm, 65 lm/W

213G 2-13W GU24 CFL, elec. NPF **218G** 2-18W GU24 CFL, elec. NPF

4. DIFFUSER

STANDARD

WGL White Glass

OPTIONAL

FTG Faux Tortoiseshell Glass

5. AVAILABLE OPTIONS

BAC Buy American Compliant ENERGY STAR® (G27LED only)

