

1513 LED

STANDARD SPECIFICATIONS

SHADE

Traditional linen lampshade material with a polyethylene liner, wrapped around a steel frame.

PAN

Formed, cold rolled steel design, finished with a sturdy electroplated brushed nickel.

LED PERFORMANCE

120-277V - 3500K, 82 CRI - L70 rating - 54,000 hours

Source lumens noted. Amperage rated @ 110V input

Max ambient temperature - 40°C / 104°F

B6LED - (1) B Series board - 6W nominal, .05 A input - 643 lm - 105 lm/W

B12LED - (2) B Series boards - 12W nominal, .10 A input - 1303 lm - 108 lm/W


MOUNTING

Directly to j-box (by others). Mounting hardware included.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



DAMP



ORDERING INFORMATION

1513 -

Model

2.

3. (if required)

2. WATTAGE

B6LED 1-B Series board

B12LED 2-B Series boards

3. AVAILABLE OPTIONS

- 30K** 3000K color temperature
B6LED - 592 lm - 96 lm/W
B12LED - 1174 lm - 98 lm/W
- 40K** 4000K color temperature
B6LED - 635 lm - 103 lm/W
B12LED - 1275 lm - 106 lm/W
- BAC** Buy American Compliant
- DIM** Dimming driver (120-277V)(B12LED only)
(0-10V dimming control required)
- ES** ENERGY STAR®(B12LED only)

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

1513




A gracefully simple fixture, this single lamp wall sconce features the latest in energy efficiency.

STANDARD SPECIFICATIONS

FASCIA: Fabric lampshade material over a steel frame
PAN: Steel, brushed nickel
BALLAST: 120V NPF Electronic
LAMP: CFL, GU24 2700K

PROJECT:
MODEL #:
FIXTURE TYPE:



DISCONTINUED

CHECK FACTORY STOCK

ORDERING INFORMATION

1513 - _____ - _____
Model 2. 3. (if required)

2. WATTAGE

13G 1-13W GU24 CFL, elec. NPF
18G 1-18W GU24 CFL, elec. NPF
23G 1-23W GU24 CFL, elec. NPF
26G 1-26/27W GU24 CFL, elec. NPF

3. AVAILABLE OPTIONS

BAC Buy American Compliant
ES3 ENERGY STAR® (elec., NPF)