

# UNIVERSAL **DISCONTINUED**

## STANDARD SPECIFICATIONS

### FRAME

Injection molded, black polycarbonate frame designed to resist impact and cold weather.  
The frame is installed on the pan with hardware.

### DIFFUSER

Translucent, UV stabilized 0.080" frosted acrylic panel assembly.

### PAN

Formed, cold rolled steel design, with a zinc galvanized finish to resist corrosion.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

3500K delivered lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 397 lm.

B12 - 12W nominal, .10 A input - 810 lm.


### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:	
MODEL #:	
FIXTURE TYPE:	



DAMP



## ORDERING INFORMATION

2020 - - -  
Model 2. 3. 4. (if required)

### 2. WATTAGE

B06 6W B Series LED  
B12 12W B Series LED

### 3. COLOR TEMPERATURE

35K 3500K standard color temperature  
27K 2700K color temperature  
30K 3000K color temperature  
40K 4000K color temperature

### 4. AVAILABLE OPTIONS

90R<sup>0</sup> 90 CRI (3000K only)  
BAC<sup>1</sup> Buy American Compliant  
BBI<sup>2\*</sup> Integral Battery Backup  
DTR<sup>4</sup> Triac (Line Voltage) Dimming (120V) (B12 only)  
ECW<sup>5</sup> Extreme Cold Weather (-40°C / -40°F min.)  
ES<sup>6</sup> ENERGY STAR<sup>®</sup> (Not available in 90 CRI)  
FCL<sup>7</sup> French Canadian Labels  
TMP Tamper Resistant Hardware and Tool  
T24<sup>9</sup> Title 24 JA8 Compliant (B12 in 3000K only)

**Notes:** (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24.  
(3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24.  
(5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24.  
(8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.  
**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

**Specifications and dimensions subject to change without notice.**

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED  
2021.06.17