



---

**2083**

Modern makeover of a traditional style. This unit features a twist-lock, highly efficient diffuser and no exposed hardware.

**FINISHES**

# 2083

**DISCONTINUED**

## STANDARD SPECIFICATIONS

### HOUSING

Cold rolled 20 GA steel, formed with die punch tooling with no exposed hardware. The pan has three steel brackets which mate with the diffuser.

### DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is vacuum formed and features a secure "twist lock" tool free installation method.

### ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp – 120-277V Electronic HPF Ballast  
GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.


<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>




BN finish, RD1 diffuser



BN finish, RD2 diffuser



RD1 diffuser



RD2 diffuser



**DAMP**



## ORDERING INFORMATION

### 2083

Model                      2.                      3.                      4.                      5. (if required)

#### 2. FINISH

##### STANDARD

**BN**      Brushed Nickel

##### OPTIONAL

**BL**      Black  
**BZ**      Bronze  
**GM**      Gun Metal  
**MB**      Metallic Bronze  
**MG**      Metallic Gold  
**NT**      Nickel Tone  
**PL**      Platinum  
**WH**      White

##### CUSTOM

Provide color sample or RAL code to match

#### 3. WATTAGE

**13Q**      1-13W Quad CFL, elec. HPF  
**213Q**      2-13W Quad CFL, elec. HPF  
**18Q**      1-18W Quad CFL, elec. HPF  
**218Q**      2-18W Quad CFL, elec. HPF  
**26Q**      1-26W Quad CFL, elec. HPF  
**226Q**      2-26W Quad CFL, elec. HPF

**13G**      1-13W GU24 CFL, elec. NPF  
**213G**      2-13W GU24 CFL, elec. NPF  
**18G**      1-18W GU24 CFL, elec. NPF  
**218G**      2-18W GU24 CFL, elec. NPF

#### 4. DIFFUSER

**RD1**      Style 1 Round Diffuser  
**RD2**      Style 2 Round Diffuser

#### 5. AVAILABLE OPTIONS

**BAC**      Buy American Compliant  
**DIM1**      Dimming Ballast (120V) (Q only)  
**DIM2**      Dimming Ballast (277V) (Q only)  
**ES**      ENERGY STAR® (26Q & 226Q only)  
**OCC<sup>2</sup>**      Occupancy Sensor

##### ACCESSORIES (field installed)

**BBR<sup>1</sup>**      Remote Battery Backup (Q only)

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

2) Occupancy sensor operates with microwaves and is not recommended for use in waiting areas with elevators.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.