

2135 **DISCONTINUED**

STANDARD SPECIFICATIONS

HOUSING

Simplicity of design is the key for this injection molded polycarbonate cup style ceiling fixture.

DIFFUSER

The one piece design is an injection molded, smooth white or clear, ribbed UV stabilized acrylic. The diffuser also features molded threads, creating an effective seal when the jar is installed.

ELECTRICAL

GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 2135 series is available in two molded colors.


PROJECT:
MODEL #:
FIXTURE TYPE:



WH finish, CPA diffuser



BL finish, WA diffuser



ORDERING INFORMATION

2135 - _____ - _____ - _____ - _____ - _____
 Model 2. 3. 4. 5. (if required)

2. FINISH

BL Black
WH White

3. WATTAGE

13G 1-13W GU24 CFL, elec. NPF
18G 1-18W GU24 CFL, elec. NPF

4. DIFFUSER

CPA Clear Prismatic Acrylic
WA White Acrylic

5. AVAILABLE OPTIONS

BAC Buy American Compliant
PC Pull Chain: On, Off (120V)

Specifications and dimensions subject to change without notice.
 Consult your Brownlee Lighting representative for availability and ordering information.