2140 LED



DRY LOCATION PROJECT:

MODEL #:


FIXTURE TYPE:

Classic ceiling luminaire with clear ribbed glass diffuser.

STANDARD SPECIFICATIONS

PAN: Steel, brass plated, brushed nickel or painted finish

DIFFUSER: Clear ribbed glass





BROWNLEE LED SYSTEM

120V or 277V constant current @ 700mA 3500K, 80 CRI

10LED 10W - (1) 10W LED board - 740 lumens - 70 lumens per watt **20LED** 20W - (2) 10W LED boards - 1480 lumens - 75 lumens per watt **40LED** 40W - (4) 10W LED boards - 2960 lumens - 75 lumens per watt

DISCONTINUED

CHECK FACTORY STOCK

ORDERING INFORMATION

2140 - ___ - __ - __ - __ - __ 5. (if required)

2. SIZE

13 13" dia. 15 15" dia. 3. FINISH

STANDARD

BN Brushed Nickel

PB Polished Brass

WH White

OPTIONAL AG Antique Gold BL Black BR Brick ΒZ Bronze СВ Crème Brulee CN Chestnut DS Desert Stone Gold Dust GD GM Gun Metal IV lvy Metallic Bronze MB NT Nickel Tone OL Oak Leaf PL Platinum RB Rustic Bronze RC Rustic Copper RW Rosewood

CUSTOMProvide color sample or RAL code to match

4. WATTAGE

13 SIZE

10LED 1-10W LED board

20LED 2-10W LED boards

15 SIZE

20LED 2-10W LED boards

40LED 4-10W LED boards

AVAILABLE OPTIONS

277 277V Driver

BAC Buy American Compliant
BBI Integral Battery Backup
DIM1 Dimming Ballast (120 volt)
DIM2 Dimming Ballast (277 volt)

ACCESSORIES (field installed)

BBR Remote Battery Backup

Brownlee offers a 3 year limited warranty on all LED products.

Consult factory for details

