

# PLATFORM **DISCONTINUED**

## STANDARD SPECIFICATIONS

### HOUSING

Cold rolled steel, formed and assembled with welds and hardware, and bolted to the pan. The frame is 20 GA, ensuring a rugged, damage resistant housing.

### DIFFUSER

UV stabilized white acrylic panels held in position with construction tabs welded inside the housing.

### PAN

Formed, cold rolled steel design, finished in a high reflectance white powder coat.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 930 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1344 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 1844 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH


The 2414 series is available in all Brownlee paint finishes as a standard offering.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.



GM finish



DAMP



## ORDERING INFORMATION

**2414** - Model - 2. - 3. - 4. - 5. - 6. (if required)

### 2. SIZE

**10** 10.5" sq.  
**13** 13.5" sq.

### 3. FINISH

**STANDARD**  
**AB** Antique Bronze  
**AS** Antique Silver  
**BL** Black  
**BZ** Bronze  
**DB** Desert Bronze  
**GM** Gun Metal  
**MB** Metallic Bronze  
**MG** Metallic Gold  
**NT** Nickel Tone  
**PL** Platinum  
**WH** White

**CUSTOM**  
Provide color sample or  
RAL code to match

### 4. WATTAGE

**10 SIZE**  
**B12** 12W B Series LED  
**C17** 16W C Series LED  
**C24** 23W C Series LED

**13 SIZE**  
**B12** 12W B Series LED  
**C17** 16W C Series LED  
**C24** 23W C Series LED

### 5. COLOR TEMPERATURE

**35K** 3500K standard color temperature  
**27K** 2700K color temperature  
**30K** 3000K color temperature  
**40K** 4000K color temperature

### 6. AVAILABLE OPTIONS

**90R<sup>0</sup>** 90 CRI (3000K only)  
**BAC<sup>1</sup>** Buy American Compliant  
**DTR<sup>4</sup>** Triac (Line Voltage) Dimming (120V)  
**ES<sup>6</sup>** ENERGY STAR® (Not available in 90 CRI)  
**FCL<sup>7</sup>** French Canadian Labels  
**OCC<sup>8</sup>** Occupancy Sensor  
**T24<sup>9</sup>** Title 24 JA8 Compliant (B12 & C24 in 3000K only)

**Notes:** (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.  
**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

**Specifications and dimensions subject to change without notice.**

Consult your Brownlee Lighting representative for availability and ordering information.