# BLOCK STANDARD SPECIFICATIONS

DISCONTINUED **CONTACT FACTORY FOR AVAILABILITY REFER TO MODEL #: 5020 FOR ALTERNATE** 

**PROJECT:** 

MODEL #:

**FIXTURE TYPE:** 

## **ENDS**

Cold rolled steel, formed, welded assembly. The ends are secured with screws.

### HOUSING

Cold rolled steel, die-formed assembly. The housing can be mounted horizontal or vertical.

### DIFFUSER

Translucent, UV stabilized white acrylic. Diffuser is formed over a mold from sturdy material that can withstand minor impact without breaking.

### **LED PERFORMANCE - 3500K STANDARD**

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

3500K delivered lumens noted. Consult Brownlee.com for performance of all CCTs. H16 – 16W nominal, .14 A input – 1699 lm. Dimmable (0-10V). H25 - 25W nominal, .20 A input - 2509 lm. Dimmable (0-10V). H32 - 32W nominal, .26 A input - 3365 lm. Dimmable (0-10V).

#### MOUNTING

Fixture uses wall anchors (by others) appropriate for the mounting surface.

#### FINISH

The 5025 series is available in all Brownlee paint finishes as a standard offering.

#### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

5025							
Model		2.	3. 4.		5.	6. (if required)	
2.	SIZE	3.	FINISH	4.	WATTAGE	5.	COLOR TEMPERATURE
24 36 48	L: 24" L: 36" L: 48"	AB AS BL BZ DB	STANDARD Antique Bronze Antique Silver Black Bronze	H16 H25	24 SIZE 16W H Series LED 36 SIZE 25W H Series LED	35K 30K 40K	3500K standard color temperature 3000K color temperature 4000K color temperature
		GM MB MG NT PL WH Provi	Desert Bronze Gun Metal Metallic Bronze Metallic Gold Nickel Tone Platinum White <b>CUSTOM</b> de color sample or RAL to match	H32	<b>48 SIZE</b> 32W H Series LED	6. 90R <sup>0</sup> BAC <sup>1</sup> BBI <sup>2*</sup> DTR <sup>4</sup> ES <sup>6</sup> FCL <sup>7</sup>	Buy American Compliant Integral Battery Backup (H25 & H32 only)

Notes: (0) 90R - cannot be combined with ES. 1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC- cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24.(4) DTR - cannot be combined with BLD or T24. (B) EUP - nanotable combined with BB, BC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24.
(B) CCC - integral DN/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BB, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BB, ECV, or T24.
(B) CCC - integral DN/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BB, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) FCH/PC4 - cannot be combined with BLD or OCC.
Add'I Notes: \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **\*\*BLD** - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period. Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED 2021.11.10



24"

36"

48"

**GM** finish

5.5"



4"

