STANDARD SPECIFICATIONS



PROJECT:	
MODEL #:	
FIXTURE TYPE:	

This multiple light source series is constructed from cold rolled steel, and designed for a variety of wall applications.

DIFFUSER

Solid white glass diffuser formed in a classic style. The exterior has a matte finish, resulting in a soft glow.

ELECTRICAL

GU24 CFL, 2-prong Base 2700K lamp - 120V Electronic NPF Ballast GU24 LED, 2-prong Base 3000K lamp - 120V - Lifetime Rating: 25,000 hours

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

GU24 base compact fluorescent lamps used with an occupancy sensor may result in severely shortened lamp life and/or ballast damage.


MOUNTING

Directly to j-box (by others). Mounting hardware included. The LED version of this fixture is designed to mounted base down only.

The 5854 series is finished in a sturdy brushed nickel plating, and is available in all Brownlee finishes as an option. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

WARRANTY

The housing features a 2 year warranty against a defect in workmanship. The lamps carry a limited warranty and claims of defective products should be addressed with the lamp







ORDERING INFORMATION

5854	-		_		-	
Model		2.		3.		4. (if required)

FINISH

STANDARD

BN **Brushed Nickel**

OPTIONAL

BL Black BT **Brass Tone** ΒZ Bronze **GM** Gun Metal MB Metallic Bronze NT Nickel Tone PL Platinum WH White

CUSTOM

Provide color sample or RAL code to match

WATTAGE

G47LED 4-7W GU24 LED - 1800 lm, 65 lm/W **G410LED** 4-10W GU24 LED - 3200 lm, 80 lm/W

413G 4-13W GU24 CFL, elec. NPF 418G 4-18W GU24 CFL, elec. NPF

4. **AVAILABLE OPTIONS**

BAC **Buy American Compliant** ES ENERGY STAR® (G47LED only)

