

# 7032




Medium architectural wall light has aluminum housing and borosilicate glass diffuse for high-wattage, high-performance applications such as perimeter lighting.

## STANDARD SPECIFICATIONS

- HOUSING:** Die-cast aluminum, bronze painted finish  
**DIFFUSER:** Clear prismatic borosilicate glass  
**BALLAST:**
- 120-277V HPF Electronic
  - 120V NPF Electronic
  - 120V NPF Magnetic
  - Multi-tap HPF Magnetic
- LAMP:**
- Triple CFL, 4-pin GX24Q Base 2700K
  - High Pressure Sodium, Medium Base
  - Metal Halide, Medium Base

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>

**DISCONTINUED**  
CHECK FACTORY STOCK



## ORDERING INFORMATION

**7032** - \_\_\_\_\_ - \_\_\_\_\_  
Model            2.                            3. (if required)

## 2. WATTAGE

- |             |                             |
|-------------|-----------------------------|
| <b>26Q</b>  | 1-26W Quad CFL, elec. NPF   |
| <b>42T</b>  | 1-42W Triple CFL, elec. HPF |
| <b>70S</b>  | 70W HPS, 120V NPF           |
| <b>100S</b> | 100W HPS, 120V NPF          |
| <b>150S</b> | 150W HPS, 120V NPF          |
| <b>70M</b>  | 70W MH, Multi-tap HPF       |
| <b>100M</b> | 100W MH, Multi-tap HPF      |
| <b>150M</b> | 150W MH, Multi-tap HPF      |

## 3. AVAILABLE OPTIONS

- BAC** Buy American Compliant  
**BBI** Integral Battery Backup (Q & T only)  
**BBIC** Integral Battery Backup, Cold Weather (Q & T only)  
**ES3** ENERGY STAR® (elec., NPF) (Q only)  
**ES4** ENERGY STAR® (elec., HPF) (Q only)  
**MT** Multi-Tap Ballast (S only)  
**PO1** Photo Control (120 volt)  
**PO2** Photo Control (208,240,277 volt)  
**QR** Quartz Re-strike (S & M only)  
**UNV** 120-277V (50/60 Hz), elec. HPF (Q only)

### ACCESSORIES (field installed)

- BBR** Remote Battery Backup (Q & T only)  
**BBRC** Remote Battery Backup, Cold Weather (Q & T only)

**Note:** *BBI and BBR options have an operating temperature of +32°F to +122°F. Cold weather options BBIC and BBRC have an operating temperature of -4°F to +131°F.*