

7165




Economical compact fluorescent canopy mount design suited for a variety of outdoor security applications.

STANDARD SPECIFICATIONS

- HOUSING:** Formed cold rolled steel, bronze or white painted finish
DIFFUSER: Clear prismatic polycarbonate
BALLAST:
 - 120V NPF Magnetic
 - 120V NPF Electronic**LAMP:**
 - CFL, 2-pin GX23 Base 2700K
 - Quad CFL, 4-pin G24Q Base 2700K
 - CFL, GU24 2700K

PROJECT:
MODEL #:
FIXTURE TYPE:



DISCONTINUED

CHECK FACTORY STOCK

ORDERING INFORMATION

7165 - _____ - _____ - _____
 Model 2. 3. 4. (if required)

2. FINISH

- BZ** Bronze
WH White

3. WATTAGE

- 13** 1-13W CFL, mag.
213 2-13W CFL, mag.

26Q 1-26W Quad CFL, elec. NPF

213G 2-13W GU24 CFL, elec. NPF
26G 1-26W GU24 CFL, elec. NPF

4. AVAILABLE OPTIONS

- BAC** Buy American Compliant
ES3 ENERGY STAR® (elec., NPF) (Q & G only)
ES4 ENERGY STAR® (elec., HPF) (Q only)
PO1 Photo Control (120 volt)
PO2 Photo Control (208,240,277 volt)
T Tamper Resistant Hardware and Tool
UNV 120-277V (50/60 Hz), elec. HPF (Q only)

ACCESSORIES (field installed)

- BBR** Remote Battery Backup (Q only)
BBRC Remote Battery Backup, Cold Weather (Q only)

Note: BBI and BBR options have an operating temperature of +32°F to +122°F. Cold weather options BBIC and BBRC have an operating temperature of -4°F to +131°F.