

7193




| |
|----------------------|
| PROJECT: |
| MODEL #: |
| FIXTURE TYPE: |

Rugged heavy duty outdoor wall fixture featuring non-yellowing molded borosilicate glass and diecast aluminum housing.

STANDARD SPECIFICATIONS

- HOUSING:** Die-cast aluminum, black painted finish
DIFFUSER: Clear prismatic borosilicate glass
BALLAST:
- 120V NPF Magnetic
 - 120V HPF Electronic
 - 120-277V HPF Electronic
 - Multi-tap HPF Magnetic
- LAMP:**
- Quad CFL, 4-pin G24Q Base 2700K
 - Triple CFL, 4-pin GX24Q Base 2700K
 - High Pressure Sodium, Medium Base
 - Metal Halide, Medium Base



DISCONTINUED
CHECK FACTORY STOCK

ORDERING INFORMATION

7193 - _____ - _____
Model 2. 3. (if required)

2. WATTAGE

- 226Q** 2-26W Quad CFL, elec. NPF
42T 1-42W Triple CFL, elec. HPF
242T 2-42W Triple CFL, elec. HPF
70S 70W HPS, 120V NPF
70M 70W MH, Multi-tap HPF

3. OPTIONS & ACCESSORIES

- BAC** Buy American Compliant
ES3 ENERGY STAR® (elec., NPF) (Q only)
ES4 ENERGY STAR® (elec., HPF) (Q only)
MT Multi-tap Ballast (S only)
UNV 120-277V (50/60 Hz), elec. HPF (Q only)

ACCESSORIES (field installed)

- BBR** Remote Battery Backup (Q & T only)
BBRC Remote Battery Backup, Cold Weather (Q & T only)

Note: BBI and BBR options have an operating temperature of +32°F to +122°F. Cold weather options BBIC and BBRC have an operating temperature of -4°F to +131°F.