

# SHORE

## STANDARD SPECIFICATIONS

### HOUSING

The coastal friendly series features one piece, injection molded construction from high quality UV resistant polycarbonate material. The housing is suitable for exposure to water in accordance to UL 746C and is attached to the mounting plate using stainless steel screws.

### MOUNTING PLATE

The plate is built from the same quality polycarbonate material as the housing, and all internal components are fastened using stainless steel hardware.

### DIFFUSER

UV resistant white acrylic, bonded to the housing.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input  
Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.  
B06 - 6W nominal, .05 A input - 445 lm. Non-dimming.  
B12 - 12W nominal, .10 A input - 879 lm. Dimmable (0-10V).

### MOUNTING

The 7319 is designed to be mounted directly to a j-box (by others). Mounting hardware included. Must be mounted in the downward orientation as pictured on spec sheet

### FINISH

The 7319 is standard in a custom white finish. Select Brownlee paint finishes are also available as an option.

### WARRANTY

3 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

**7319** -        -        -        -        -         
Model                      2.                      3.                      4.                      5. (if required)

### 2. FINISH

**STANDARD**  
**WH** White

**OPTIONAL**  
**BL** Black  
**BZ** Bronze  
**GM** Gun Metal  
**MB** Metallic Bronze  
**NT** Nickel Tone  
**PL** Platinum

**CUSTOM**  
Provide color sample or RAL  
code to match

### 3. WATTAGE

**B06** 6W B Series LED  
**B12** 12W B Series LED

### 4. COLOR TEMPERATURE


**35K** 3500K standard color temperature  
**27K** 2700K color temperature  
**30K** 3000K color temperature  
**40K** 4000K color temperature

### 5. AVAILABLE OPTIONS

**BAC**<sup>1</sup> Buy American Compliant  
**DTR**<sup>4</sup> Triac (Line Voltage) Dimming (120V) (All except B06)  
**ES**<sup>6</sup> ENERGY STAR®  
**FCL**<sup>7</sup> French Canadian Labels  
**PO1** Photo Control (120V)  
**PO2** Photo Control (208, 240, 277V)  
**T24**<sup>9</sup> Title 24 JA8 Compliant (B12 in 3000K only)



WH Finish



**WET**  
Down mount



**Notes:** (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT.  
(3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD or T24.  
(5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC.  
(8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with DTR or ES.  
(10) BBS - cannot be combined with BLD, ECW, EXT, or OCC. (11) PCH/PC4 - cannot be combined with BLD or OCC.  
**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50%, 30%, 20% or 10%. 3: Remain in continuous dimmed state or turn off after set period.

**Specifications and dimensions subject to change without notice.**  
Consult your Brownlee Lighting representative for availability and ordering information.