# STANDARD SPECIFICATIONS

	PROJECT:
	MODEL #:
	FIXTURE TYPE:

## **SHROUD**

Sturdy, 0.060" aluminum roll formed to surround the polycarbonate housing. The shroud is attached to a mounting plate secured to the wall. The shroud also has a flexible UV stabilized diffuser designed to withstand minor impact without breaking.

The injection molded aluminum housing is designed to withstand rugged environments. The cover plate is punched from galvanized steel.

Semi-polished aluminum, one piece die-formed material.

## **DIFFUSER**

UV stabilized polycarbonate, injection molded in a clear 0.125" thick prismatic diffuser.

# **LED PERFORMANCE - 3500K STANDARD**

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Standard 3500K source lumens noted. Consult Brownlee.com for performance of all CCTs. B12LED - 12W nominal, .10 A input - 1422 lm - 120 lm/W

## MOUNTING

The housing mounts directly to a j-box (by others). Mounting hardware included. The mounting plate is installed on the wall via (4) anchors (by others), that are appropriate for the mounting surface. The shroud attaches to the plate using the included hardware.

### **FINISH**

The 7501 series is available in all Brownlee paint finishes as a standard offering.

5 year limited warranty on this LED product. Consult factory for details.

# ORDERING INFORMATION

7501 Model

7.5" 15.25









# 2. FINISH

### **STANDARD** Antique Bronze AB

AS Antique Silver BL Black BT **Brass Tone** ΒZ Bronze DB Desert Bronze GM Gun Metal MB Metallic Bronze NT Nickel Tone PL Platinum WH White

## **CUSTOM**

Provide color sample or RAL code to match

# WATTAGE

**B12LED** 2-B Series boards

4. (if required)

# **AVAILABLE OPTIONS**

35K 3500K standard color temperature 27K 2700K color temperature 30K 3000K color temperature 40K 4000K color temperature BAC **Buy American Compliant** DIM Dimming driver (120-277V) (0-10V dimming control required) DTR Triac (Line Voltage) Dimming (120V) **ECW** Extreme Cold Weather (-40°C / -40°F min.) ES **ENERGY STAR®** Τ Tamper Resistant Hardware and Tool



# **7501**

# STANDARD SPECIFICATIONS

# CHECK FACTORY STOCK

PROJECT:	
MODEL #:	
FIXTURE TYPE:	

# **SHROUD**

Sturdy, 0.060" aluminum roll formed to surround the polycarbonate housing. The shroud is attached to a mounting plate secured to the wall. The shroud also has a flexible UV stabilized diffuser designed to withstand minor impact without breaking.

### HOUSING

The injection molded aluminum housing is designed to withstand rugged environments. The cover plate is punched from galvanized steel.

### REFLECTOR

Semi-polished aluminum, one piece die-formed material.

### **DIFFUSER**

UV stabilized polycarbonate, injection molded in a clear 0.125" thick prismatic diffuser.

## **ELECTRICAL**

CFL, 2-pin GX23 Base 2700K lamp - 120V Magnetic NPF Ballast

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

# **MOUNTING**

The housing mounts directly to a j-box (by others). Mounting hardware included. The mounting plate is installed on the wall via (4) anchors (by others), that are appropriate for the mounting surface. The shroud attaches to the plate using the included hardware.

### FINISH

The 7501 series is available in all Brownlee paint finishes as a standard offering.



# ORDERING INFORMATION

	ISH

STANDARD							
AB	Antique Bronze						
AC	Antique Copper						
AG	Antique Gold						
AS	Antique Silver						
BL	Black						
BR	Brick						
BT	Brass Tone						
ΒZ	Bronze						
DB	Desert Bronze						
DS	Desert Stone						
GM	Gun Metal						
MB	Metallic Bronze						
NT	Nickel Tone						
0L	Oak Leaf						
PL	Platinum						
RB	Rustic Bronze						
RC	Rustic Copper						
TB	Textured Black						
WH	White						

# **CUSTOM**

Provide color sample or RAL code to match

# 3. WATTAGE

13	1-13W CFL,	mag.
213	2-13W CFL,	mag.

# 4. AVAILABLE OPTIONS

BAC Buy American Compliant
T Tamper Resistant Hardware and Tool

