STRIDER

PROJECT:	
MODEL #:	
FIXTURE TYPE:	

STANDARD SPECIFICATIONS

FRAME
Cold rolled steel, treated with a rust inhibiting zinc coating, roll formed and assembled with construction tabs and hardware.

DIFFUSER
Translucent, UV stabilized, white acrylic. The material is flexible to withstand minor impact without breaking.

LED PERFORMANCE - 3500K STANDARD
120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.
B06 - 6W nominal, .05 A input - 572 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 1131 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 797 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 1634 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 2242 lm. Dimmable (0-10V).

MOUNTING
Directly to j-box (by others). Mounting hardware included.

FINISH
The 1350 series is available in all Brownlee paint finishes as a standard offering.

WARRANTY
5 year limited warranty on this LED product. Consult factory for details.

DB finish

NT finish



DAMP

ADA

SUPPORTS T24 COMPLIANCE

ORDERING INFORMATION

1350 - _____ - _____ - _____ - _____

Model | 2. | 3. | 4. | 5.

2. FINISH

STANDARD

AB	Antique Bronze
AS	Antique Silver
BL	Black
BZ	Bronze
DB	Desert Bronze
GM	Gun Metal
MB	Metallic Bronze
MG	Metallic Gold
NT	Nickel Tone
PL	Platinum
WH	White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

B06	6W B Series LED
B12	12W B Series LED
C09	9W C Series LED
C17	16W C Series LED
C24	23W C Series LED

4. COLOR TEMPERATURE

35K	3500K standard color temperature
27K	2700K color temperature
30K	3000K color temperature
40K	4000K color temperature

5. AVAILABLE OPTIONS

90R[0]	90 CRI (3000K only)
BAC[1]	Buy American Compliant
BBI[2*]	Integral Battery Backup
DTR[4]	Triac (Line Voltage) Dimming (120V) (All except B06)
ES[6]	ENERGY STAR® (Not available in 90 CRI)
EXT	Extended Housing (Does not include battery, intended to match BBI aesthetic)
FCL[7]	French Canadian Labels
T24[9]	Title 24 JA8 Compliant (B12 & C24 in 3000K only)
TBC	Top/Bottom Covers (Perforated)

Notes: (0) 90R - cannot be combined with ES. **1) BAC** - cannot be combined with FCL. **(2) BBI/BBS/BBC**- cannot be combined with ECW, EXT, or T24. **(3) BLD** - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. **(4) DTR** - cannot be combined with BLD or T24. **(5) ECW** - cannot be combined with BBI, BBC, or DTR. **(6) ES** - cannot be combined with 90R or T24. **(7) FCL** - cannot be combined with BAC or T24. **(8) OCC** - integral ON/OFF occupancy sensor. **(9) T24** - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. **(10) BBS** - cannot be combined with BLD, ECW, EXT, OCC, or T24. **(11) PCH/PC4** - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. ****BLD** - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.
Consult your Brownlee Lighting representative for availability and ordering information.

BROWNLEE LIGHTING
www.brownlee.com

REVISED 2020.12.22