

LUMIBOX

STANDARD SPECIFICATIONS

HOUSING/FRAME

Assembled from formed cold rolled steel, this simple design is a classic look that blends with any décor.

MOUNT PAN

Manufactured using cold rolled steel with a baked on, high reflectance white finish.

DIFFUSER

Matte white acrylic diffuser covers the front, sides, top, and bottom of fixture, allowing for omnidirectional light output. Contact factory for custom color options.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 548 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 1084 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 764 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 1566 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 2148 lm. Dimmable (0-10V).
C37 - 35W nominal, .30 A input - 4380 lm. Dimmable (0-10V).

MOUNTING

The 1454 is designed to be mounted directly to a j-box (by others).
The 27" version has additional holes for anchor bolts (by others) appropriate for the mounting surface.

FINISH

The 1454 series is available in all Brownlee finishes as a standard offering.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



NT finish, WHA diffuser



DAMP



ORDERING INFORMATION

1454 - Model - 2. - 3. - 4. - 5. - 6. - 7. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. DIFFUSER	6. COLOR TEMPERATURE
15 L: 15"	STANDARD	15 SIZE	WHA White Acrylic	35K 3500K standard color temperature
27 L: 27"	AB Antique Bronze	B06 6W B Series LED	*NOTE: previously offered diffuser options (WHL, BMB, LMG, etc.) have been discontinued from this model, but can be manufactured as a special if needed - contact factory.	27K 2700K color temperature
	AS Antique Silver	B12 12W B Series LED		30K 3000K color temperature
	BL Black	C09 9W C Series LED		40K 4000K color temperature
	BZ Bronze	C17 16W C Series LED		
	DB Desert Bronze	C24 23W C Series LED		
	GM Gun Metal	27 SIZE		
	MB Metallic Bronze	C37 35W C Series LED		
	MG Metallic Gold			
	NT Nickel Tone			
	PL Platinum			
	WH White			
	CUSTOM			
	Provide color sample or RAL code to match.			
				7. AVAILABLE OPTIONS
				90R⁰ 90 CRI (3000K only)
				BAC¹ Buy American Compliant
				DTR⁴ Triac (Line Voltage) Dimming (120V) (All except B06)
				ES⁶ ENERGY STAR® (Not available in 90 CRI)
				FCL⁷ French Canadian Labels
				T24⁹ Title 24 JA8 Compliant (B12 & C24 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

