

# OPAL [S2]

## STANDARD SPECIFICATIONS

### HOUSING

Cold rolled steel, formed in a die, finished with an electroplated brushed nickel coating that will withstand minor nicks and scratches.

### DIFFUSER

Glass cylinder, white finished interior and etched exterior to disguise the light source. The cylinder is bonded with adhesive to a carbon steel threaded ring that screws into the cup holder for a secure installation.

### ELECTRICAL

This model is built with a single E26 socket (25W max rated) to accept a screw-in LED lamp (lamp provided standard).

Lamp: 10W nominal, 1000 source lm nominal, 3000K, 120V, Dimmable, Type A  
Lamp Lifetime Rating: 15,000 hours (based on 4 hours per day).

Lamp Certification (if any): Energy Star qualified lamp (fixture has not been Energy Star qualified).

### MOUNTING

This series is designed to be mounted directly to a j-box (by others). Mounting hardware included. The LED version of this fixture is designed to be mounted base down only (as shown in line drawing).

### FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.


### WARRANTY

Fixture parts carry a two year limited warranty against defects in workmanship. The LED lamps carry a one year limited warranty under Brownlee. Lamp claims outside of one year should be addressed with the lamp manufacturer. Contact factory for extended warranty.

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BN finish



## ORDERING INFORMATION



DAMP



ADA

**1474** - \_\_\_\_\_  
Model                      2.                      3.                      4.

### 2. FINISH

#### STANDARD

**BN**      Brushed Nickel

#### OPTIONAL

**BL**      Black  
**BZ**      Bronze  
**GM**      Gun Metal  
**MB**      Metallic Bronze  
**MG**      Metallic Gold  
**NT**      Nickel Tone  
**PL**      Platinum  
**WH**      White

#### CUSTOM

Provide color sample or RAL code to match

### 3. SOCKET TYPE

**125N**      One 25W Max-Rated E26 Socket, **LED Lamp Provided, 10W / 1000 source lm nominal / 30K**

NOTE: Brownlee has phased out of GU24 technology. Contact factory for availability.

### 4. AVAILABLE OPTIONS

**FCL<sup>7</sup>**      French Canadian Labels  
**LLP**      Less Lamp (No lamp/bulb provided. Socket only.)

**Notes:** (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with DTR or ES. (10) BBS - cannot be combined with BLD, ECW, EXT, or OCC. (11) PCH/PC4 - cannot be combined with BLD or OCC.  
**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50%, 30%, 20% or 10%. 3: Remain in continuous dimmed state or turn off after set period.

**Specifications and dimensions subject to change without notice.**  
Consult your Brownlee Lighting representative for availability and ordering information.