

TWO-TIER

STANDARD SPECIFICATIONS

DIFFUSER

The two tier drum is a modern take on the traditional style. The UV stabilized white acrylic with fabric material bonded to the exterior.

HOUSING

Formed, cold rolled steel design, finished in a high reflectance powder coat white.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

C37 - 35W nominal, .30 A input - 3530 lm. Dimmable (0-10V).

C49 - 45W nominal, .40 A input - 4758 lm. Dimmable (0-10V).

MOUNTING

Directly to j-box (by others). Mounting hardware included.

SUSPENSION SYSTEM

The 2604 Series is available in multiple colors and four suspension methods:

CC1 - Cord & Single Cable: Both the power cord and aircraft cable can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.

CC3 - Cord & Three Cable: Both the power cord and aircraft cables can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.

SCM - Stem & Cable Mount: Steel stem in your choice of finish with three aircraft cables. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.

SSM - Single Stem Mount: Traditional pendant style. Steel stem in your choice of finish. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.

WARRANTY


5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION


PROJECT:
MODEL #:
FIXTURE TYPE:




WH finish, WHL diffuser, CC3 suspension




SSM suspension



SCM suspension



CC1 suspension



CC3 suspension



2604							
Model	2.	3.	4.	5.	6.	7.	8. (if required)
2. SIZE	24 24" dia. 30 30" dia.						
3. FINISH	CC1 & CC3 BL Black NT Nickel Tone WH White SCM & SSM BL Black BZ Bronze GM Gun Metal MB Metallic Bronze MG Metallic Gold NT Nickel Tone PL Platinum WH White	4. WATTAGE C37 35W C Series LED C49 45W C Series LED 5. DIFFUSER NAL Natural Linen WHL White Linen Note: Contact factory for previously discontinued diffuser options.	6. SUSPENSION CC1 Cord & Single Cable CC3 Cord & Three Cable SCM Stem & Cable Mount SSM Single Stem Mount	7. COLOR TEMPERATURE 35K 3500K color temperature 27K 2700K color temperature 30K 3000K color temperature 40K 4000K color temperature	8. AVAILABLE OPTIONS 90R⁰ 90 CRI (3000K only) BAC¹ Buy American Compliant CE1 3' - 10' Cord/Cable Extension (CC1 & CC3 only) CE2 10' - 20' Cord/Cable Extension (CC1 & CC3 only) DTR⁴ Triac (Line Voltage) Dimming (120V) ES⁶ ENERGY STAR® (Not available in 90 CRI) FCL⁷ French Canadian Labels T24⁹ Title 24 JA8 Compliant (C49 in 3000K only)		
ACCESSORIES (field installed - order separately)							
390001xx SCM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)							
390002xx SSM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)							
320029WHA Top Cover Set: 24 size, White Acrylic							
320030WHA Top Cover Set: 30 size, White Acrylic							

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

