

BOUNCE-RD

STANDARD SPECIFICATIONS

HOUSING

Injection molded polycarbonate, one piece housing with a uniform .08" thickness. The color is molded throughout.

DIFFUSER

UV stabilized white polycarbonate, injection molded with a thickness of .08". The inside top of the diffuser is molded with small prisms to disguise the light source.

REFLECTOR

Cold rolled steel finished with a powder coat high reflectance white finish

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Amperage rated @ 110V input
 Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

- B06 - 6W nominal, .05 A input - 544 lm. Non-dimming.
- B12 - 12W nominal, .10 A input - 1075 lm. Dimmable (0-10V).
- C09 - 9W nominal, .10 A input - 758 lm. Dimmable (0-10V).
- C17 - 16W nominal, .15 A input - 1553 lm. Dimmable (0-10V).
- C24 - 23W nominal, .20 A input - 2131 lm. Dimmable (0-10V).

MOUNTING

Directly to j-box (by others). Mounting hardware included. Not available with conduit entry.

FINISH

Brownlee offers two standard molded finishes.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

7156 - _____
 Model 2. 3. 4. 5. (if required)

2. FINISH

BL Black
WH White

3. WATTAGE

B06 6W B Series LED
B12 12W B Series LED

C09 9W C Series LED
C17 16W C Series LED
C24 23W C Series LED

4. COLOR TEMPERATURE

35K 3500K standard color temperature
27K 2700K color temperature
30K 3000K color temperature
40K 4000K color temperature


5. AVAILABLE OPTIONS

BAC¹ Buy American Compliant
BLD^{3**} Bi-Level Dimming (All except B06)
DTR⁴ Triac (Line Voltage) Dimming (120V) (All except B06)
ECW⁵ Extreme Cold Weather (-40°C / -40°F min.)
ES⁶ ENERGY STAR®
FCL⁷ French Canadian Labels
OCC⁸ Occupancy Sensor (B series only)
T24⁹ Title 24 JA8 Compliant (B12 & C24 in 3000K only)

PROJECT:
MODEL #:
FIXTURE TYPE:



WH finish



WET



Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24.
 (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24.
 (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24.
 (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.
Specifications and dimensions subject to change without notice.
 Consult your Brownlee Lighting representative for availability and ordering information.