

SHORE [CUTOFF]



27K/30K ONLY

PROJECT:

MODEL #:

FIXTURE TYPE:

STANDARD SPECIFICATIONS

HOUSING

The coastal friendly series features one piece, injection molded construction from high quality UV resistant polycarbonate material. The housing is suitable for exposure to water in accordance to UL 746C and is attached to the mounting plate using stainless steel screws. Full cut-off design.

MOUNTING PLATE

The plate is built from the same quality polycarbonate material as the housing, and all internal components are fastened using stainless steel hardware.

DIFFUSER

UV resistant white or clear acrylic, bonded to the housing.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 813 lm. Non-dimming.

B12 - 12W nominal, .10 A input - 1607 lm. Dimmable (0-10V).

MOUNTING

The 7317 must be positioned downwards (downlight only) and mounts directly to a j-box (by others). Mounting hardware included.

FINISH


The 7317 is standard in a white finish. Select Brownlee paint finishes are also available as an option.

WARRANTY

3 year limited warranty on this LED product. Consult factory for details.



BZ finish, WHA diffuser



WET



ORDERING INFORMATION

7317 - - - - - - -
 Model 2. 3. 4. 5. 6. (if required)

2. FINISH

STANDARD
WH White

OPTIONAL
BL Black
BZ Bronze
CR Cream
GM Gun Metal
MB Metallic Bronze
NT Nickel Tone
PL Platinum

CUSTOM
 Provide color sample or RAL code to match

3. WATTAGE

B06 6W B Series LED
B12 12W B Series LED

4. DIFFUSER

WHA White Acrylic
CLA Clear Acrylic

5. COLOR TEMPERATURE

35K 3500K standard color temperature
27K 2700K color temperature
30K 3000K color temperature
40K 4000K color temperature

6. AVAILABLE OPTIONS

BAC¹ Buy American Compliant
DTR⁴ Triac (Line Voltage) Dimming (120V) (B12 only)
ES⁶ ENERGY STAR®
FCL⁷ French Canadian Labels
PO1 Photo Control (120V)
PO2 Photo Control (208, 240, 277V)
T24⁹ Title 24 JA8 Compliant (B12 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED
 2020.12.28